§442.43

the corresponding limitation specified in §442.41.

§442.43 Effluent limitations attainable by the application of best available technology economically achievable (BAT). [Reserved]

§ 442.44 New source performance standards (NSPS).

Any new point source subject to this subpart must achieve the following performance standards: Standards for BOD₅, TSS, oil and grease (HEM) and pH are the same as the corresponding limitation specified in §442.41.

PART 443—EFFLUENT LIMITATIONS
GUIDELINES FOR EXISTING
SOURCES AND STANDARDS OF
PERFORMANCE AND
PRETREATMENT STANDARDS FOR
NEW SOURCES FOR THE PAVING
AND ROOFING MATERIALS (TARS
AND ASPHALT) POINT SOURCE
CATEGORY

Subpart A—Asphalt Emulsion Subcategory

Sec

443.10 Applicability; description of the asphalt emulsion subcategory.

443.11 Specialized definitions.

- 443.12 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 443.13 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

443.14 [Reserved]

- 443.15 Standards of performance for new sources.
- 443.16 Pretreatment standards for new sources.

Subpart B—Asphalt Concrete Subcategory

- 443.20 Applicability; description of the asphalt concrete subcategory.
- $443.21 \quad {\tt Specialized \ definitions.}$
- 443.22 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 443.23 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best

available technology economically achievable.

443.24 [Reserved]

443.25 Standards of performance for new sources

443.26 Pretreatment standard for new sources.

Subpart C—Asphalt Roofing Subcategory

443.30 Applicability; description of the asphalt roofing subcategory.

443.31 Specialized definitions.

- 443.32 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 443.33 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

443.34 [Reserved]

- 443.35 Standards of performance for new sources.
- 443.36 Pretreatment standard for new sources.

Subpart D—Linoleum and Printed Asphalt Felt Subcategory

- 443.40 Applicability; description of the linoleum and printed asphalt felt subcategory.
- 443.41 Specialized definitions.
- 443.42 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available.
- 443.43 Effluent limitations guidelines representing the degree of effluent reduction attainable by the application of the best available technology economically achievable.

443.44 [Reserved]

- 443.45 Standards of performance for new sources.
- 443.46 Pretreatment standards for new sources.

AUTHORITY: Secs. 301, 304 (b) and (c), 306 (b) and (c) and 307(c), Federal Water Pollution Control Act, as amended (the Act); 33 U.S.C. 1251, 1311, 1314 (b) and (c), 1316 (b) and (c), 1317(c), 86 Stat. 816 et seq.; Pub. L. 92-500.

SOURCE: 40 FR 31191, July 24, 1975, unless otherwise noted.